

■ 特性 Features:

- 输入电压范围: 90-264Vac/127-370Vdc
The input voltage range : 100-240Vac
- 工作温度高达 70℃
Operating temperature up to 70℃
- 4242Vdc 高隔离电压
4242Vdc high isolation voltage
- 输出低纹波噪声
Low ripple noise output
- 电源输出 LED 指示灯
Power output LED indicator
- 自然风冷散热
Cooling by free air convection
- 输出电压值可调
The output voltage is adjustable
- 输出短路、过流、过压、过温保护功能
With OSP、OCP、OVP、OTP functions
- 满足 5000m 海拔应用(备注3)
Meet 5000m altitude application (Note 3)
- 100%高温老化
100% high temperature aging
- 满足 5G 振动测试
Meet 5G vibration test
- 符合 IEC/EN/UL62368、GB4943、GB9254、EN62477 等认证标准
Comply with IEC/EN/UL62368, GB4943, GB9254 and EN62477 Etc.certification standards
- 输出双重过压保护(可选)
Output double OVP (optional)
- 高可靠性, 基板三防漆工艺(可选)
High reliability, substrate three anti-paint process (optional)
- 质保期: 3 年
Warranty: 3 Years



■ 应用 Applications:

- 工业控制或自动化装置
Industrial control or automation devices
- 电子仪器, 设备和装置
Electronic instruments, equipment and devices
- 机械和电气设备
Mechanical and electrical equipment
- 老化设备
Burn-in equipment

■ 描述 Description:

ERS75W 系列是一款 75W 单组输出 AC 转 DC 电源, 100-240V 交流输入, 整系列提供 5V, 12V, 15V, 24V, 36V 和 48V 直流隔离输出; 30mm 极薄外型设计, 具有完整的保护功能, EMC 性能好, 高可靠性, 高性价比, 安全隔离等优点。产品符合 IEC/UL/EN/BS EN62368、EN61558、GB4943、BIS IS13252、EN62477 等国际安全法规, 符合欧盟 RoHS2.0 指令, 是一款极具性价比的工业电源。

ERS75W series is a 75W single output AC to DC PSU, 100-240Vac input, The whole series provides 5V, 12V, 15V, 24V, 36V and 48V DC isolated output; Advantages such as 30mm extremely thin design; With complete protection function; Excellent EMC performance, high reliability, high cost performance, security isolation and so on. Products comply with IEC/UL/EN/BS EN62368、EN61558、GB4943、BIS IS13252、EN62477 international safety standards and EU RoHS2.0 directive; It is a cost-effective industrial PSU.

选型规格 Model Selection

功率段 POWER	产品型号 MODEL	输出功率 Pout	输入电压 Vin	输出电压 Vout	输出电流 Iout	效率 (%) EFF.	安规认证 SAFETY
75W	GW-ERS75W-5	65W	90-264Vac/ 127-370Vdc	5V	13A	81	CQC, CB, UL
	GW-ERS75W-12	75W		12V	6.25A	86	
	GW-ERS75W-15	75W		15V	5A	88	
	GW-ERS75W-24	76.8W		24V	3.2A	89	
	GW-ERS75W-36	74.88W		36V	2.08A	88	
	GW-ERS75W-48	74.88W		48V	1.56A	90	

*其它安规需求认证中 Other safety requirements are pending certification.



通用参数 General Specification

型号 MODEL		ERS75W-5	ERS75W-12	ERS75W-15	ERS75W-24	ERS75W-36	ERS75W-48
输出 Output	输出电压 Output Voltage	5V	12V	15V	24V	36V	48V
	额定电流 Output Current	13A	6.25A	5A	3.2A	2.08A	1.56A
	电流范围 Current Range	0~13A	0~6.25A	0~5A	0~3.2A	0~2.08A	0~1.56A
	额定功率 Output Power	65W	75W	75W	76.8W	74.88W	74.88W
	纹波与噪声 Ripple and Noise(备注 6)	100mV	100mV	100mV	120mV	120mV	120mV
	电压调整范围 Adj-voltage range	4.75~5.25V	10.2~13.8V	13.5~17.3V	21.6~28.8V	32.4~39.6V	43.2~52.8V
	稳压精度 Voltage stability(备注 2)	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%
	线性调整率 Line regulation	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
	负载调整率 Load regulation	±1.0%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
	保持时间	50ms (230Vac/100% load), 10ms (115Vac/80% load)					

	Hold-up time						
	启动时间						
	Startup time	≤3s （115Vac /230Vac ； 100% load）					
输入 Input	电压范围	90~264Vac					
	Voltage Range						
	频率范围	47~63Hz					
	Frequency Range						
	输入电流	1.8A / 100Vac					
	Input Current						
	浪涌电流 Inrush	100A / 230Vac, Cold start					
	Current						
	效率 Efficiency	82.5%	88.0%	88.5%	89.0%	90.0%	90.5%
保护 Protections	过电压 OVP	5.6~10V	13.8~17V	17.3~22.5V	28.8~36V	43.2~54V	55.2~64.8V
	过负载 OCP	14.3~22.1A	9.3~13.3A	7.37~10.72A	5~6.72A	3~4.76A	2.53~3.91A
	过温度 OTP	打嗝模式，异常条件移除后可自动恢复 Hiccup mode, The PSU can be Auto-recovered when the fault is removed					
	短路 OSP	打嗝模式，异常条件移除后可自动恢复 Hiccup mode, The PSU can be Auto-recovered when the fault is removed					
环境 Environmental	工作温度 Operating Temperature	-25 ~ +70℃ 请参考降额曲线 Refer to the derating curve					
	工作湿度 Operating Humidity	20% ~ 90% RH，无冷凝 Non-condensing					
	存储温度 Storage Temperature	-40 ~ +85℃					
	存储湿度 Storage humidity	5% ~ 95% RH，无冷凝 Non-condensing					
安规 Safety	安全规范 safety standards	IEC/UL/EN/BS EN62368、EN61558、GB4943、BIS IS13252、EN62477					
	耐压 Hi-pot	I/P - O/P: 3000Vac/4242Vdc; I/P - FG: 1500Vac/2500Vdc; O/P - FG: 500Vac/707Vdc					
	绝缘阻抗 Insulating resistance	≥10Mohm (500VDC / 25℃ / 90% RH)					
	漏电流	<1.0mA / 240Vac					
	Leakage Current						
	静电放电 ESD	IEC/EN61000-4-2, CLASS B; Contact1 ±8KV / Air ±15KV ;					
	电磁兼容 EMC	CISPR32 / EN55032, CLASS B					
其它 Others	质保期 Warranty	3Years					
	MTBF	Telcordia SR-332 (Bellcore) ≥500K hrs					
	尺寸 SIZE	129mm * 97mm * 30mm (L * W * H)					
	包装 Packing	0.250KG; 40PCS/Box					
	1. 如未特别说明，所有规格参数均在输入为 230Vac，额定负载，25℃环境温度下进行测量，详见测试报告。 Unless otherwise specified,all spec.are measured at 230Vac,rated load, Ta=25℃, Please refer to the test report. 2. 输出电压的精度包含设定误差、线性调整率和负载调整率						


备注 Remark	The voltage stability includes setting error, linear regulation and load regulation
	3. 当产品工作于海拔 2000m 以上时, 环境温度需降额 5°C/1000m When the power supply is working above an altitude of 2000m, the Ta must be derated by 5°C/1000m
	4. 此电源不符合 EN61000-3-2 标准中规定的谐波电流要求, 如应用无谐波电流要求或可自行解决谐波电流问题, 可选型本产品。 This power supply don't meet the harmonic requirements in EN61000-3-2 standard. It can be selected if no harmonic requirements are applied or this problems can be solved by themselves.
	5. 产品在任何稳态工作条件下, 总功率不应超出标示的额定功率且输出电流不应超出额定输出电流。 Under any operating conditions, the total power should not exceed the rated power indicated and the output current should not exceed the rated output current.
	6. 纹波和噪声的测试方法采用双绞线连接, 输出并联 47uF 低 ESR 电容和 0.1uF 陶瓷电容, 在 20MHz 带宽下进行量测。 The test method of ripple and noise is connected by twisted pair, the output is in parallel with 47uF low ESR capacitor and 0.1uF ceramic capacitor, and the measurement is carried out at 20MHz bandwidth.
	*产品免责声明: 产品最终解释权归长城电源技术有限公司所有 详细请参阅网址 https://www.gwpst.cn *Disclaimer: The final interpretation rights of the product belong to Great Wall Power Supply Technology Co., Ltd. Details please refer to https://www.gwpst.com

■ 降额曲线 Derating Curve



结构参数 Mechanical Overview

■ 结构尺寸 Shape Size




端子引脚描述 Terminal PIN Description

引脚编号 Pin number	1	2	3	4	5
引脚功能 Pin Feature	AC/L	AC/N	FG	Vout -	Vout +

孔编号	推荐螺丝型号	最大穿孔深度 L	推荐安装扭矩
①	M3	4mm	4~6Kgf.cm

■ 方框图 Block Diagram



* 安装手册请查阅网址: <https://www.gwpst.cn>

* Installation manual, please refer to web.: <https://www.gwpst.com>